T15

FLEXIBLE HOSE IN PVC AND STEEL WIRE
TEMPERATURE UP TO 85 °C



Applications Fumes and dust extraction

Use Extraction systems

DESCRIPTION
Highly flexible hose suited for extraction of fumes and dust, resistant to temperatures 0-85 °C.
Good resistance to chemicals.
RoHS compliance.

FEATURES
Spring steel wire coated with plastics.
Soft PVC hose.

T15 FLEXIBLE HOSE

TECHNICAL FEATURES

Code	Internal Ø	External Ø	Overpressure	No-load pressure	Bending radius	Weight	Available length
	mm	mm	bar	bar	mm	kg/m	m
T1500000000032	32	38	1,5	0,20	16	0,28	15
T1500000000041	41	47	1,4	0,18	21	0,37	15
T1500000000051	51	57	1,3	0,15	26	0,46	15
T1500000000063	63	69	1,0	0,14	31	0,53	15
T1500000000075	75	82	0,8	0,10	38	0,68	15
T1500000000080	80	86	0,7	0,09	40	0,83	15
T1500000000100	100	106	0,6	0,08	52	1,00	15

Tel. +39 049 641 200 | info@aerservice.com | www.aerservice.com

DESCRIPTION

Model	Code	Description
	T1500000000032	T15 flexible hose - Ø 30 mm
	T1500000000041	T15 flexible hose - Ø 40 mm
	T1500000000051	T15 flexible hose - Ø 50 mm
	T1500000000063	T15 flexible hose - Ø 60 mm
	T1500000000075	T15 flexible hose - Ø 75 mm
	T1500000000080	T15 flexible hose - Ø 80 mm
	T1500000000100	T15 flexible hose - Ø 100 mm

ACCESSORIES

Coupling	Code	Description
	ACC0T15AA00032	Thread coupling for flexible hose T15 Ø 30 mm - L. 100 mm (50 mm + thread 45 mm) - Temperature 0-70 °C
	ACC0T15AA00041	Thread coupling for flexible hose T15 Ø 40 mm - L. 100 mm (50 mm + thread 45 mm) - Temperature 0-70 °C
	ACC0T15AA00051	Thread coupling for flexible hose T15 Ø 50 mm - L. 100 mm (50 mm + thread 45 mm) - Temperature 0-70 °C
	ACC0T15AA00063	Thread coupling for flexible hose T15 Ø 60 mm - L. 100 mm (50 mm + thread 45 mm) - Temperature 0-70 °C
	ACC0T15AA00075	Thread coupling for flexible hose T15 Ø 75 mm - L. 100 mm (50 mm + thread 45 mm) - Temperature 0-70 °C